



Bearing equipment manufacturing Co., Ltd



32338 Bearing 2D drawings and 3D CAD models

32338 NSK Double direction thrust bearings

Bearing No. 32338

Size	190x400x140 mm
Bore Diameter	190 mm
Outer Diameter	400 mm
Width	140 mm
d	190 mm
D	400 mm
T	140 mm
B	132 mm
C	109 mm
a	102,7 mm
r min.	6 mm
r1 min.	5 mm
da min.	229 mm
Da min	332 mm
Da max.	378 mm
db max.	243 mm
Db min.	375 mm
ra max.	5 mm
rb max.	4 mm
Weight	78,9 Kg
Basic dynamic load rating (C)	1660 kN
Basic static load rating (C0)	2580 kN
(Grease) Lubrication Speed	850 r/min
(Oil) Lubrication Speed	1200 r/min
Calculation factor (e)	0,37
Calculation factor (Y0)	0,88



Bearing equipment manufacturing Co., Ltd

Category	Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	74.5
Product Group	B04334
LangID	1
outer r	5
D_	400
TC-BET22	50
TC-BET21	3
TC-BET23	0
inner r	6
mass	78.9
GRS rpm	850
D_b	375
Cr	169000
TC-RA	770.828
DE_	347.177
T-ALP23	0
db	243
T-ALP22	0
Prod_Type3	TRBSR_MD_A
da	229
T-ALP21	28
Iso	-
ALPHA_	14
SDM_	301.013
SBRG	23
D_a2	332
hidYobi	32338
Y1	1.6



Bearing equipment manufacturing Co., Ltd

D_a1	378
B_	132
hidTable	ecat_NSTPRM
Oil rpm	1200
C0r	263000
Y0	0.88
TC-SLR	97
inner ra	5
outer rb	4
C0	2580
Sa	11
Sb	31
e	0.37
DA_	48.329
Z_	16
C_	109
yobi	32338
TC-DA1	51.558
TC-DA2	45.099
KBRG	3111
DI_	254.848